









LED Linear Lighting System



Material	Aluminum+PMMA Lens/ PC Cover											
Length(mm)	568				1416				2832		4248	
Power(W)	16	26	32	32	40	65	80	65	80	120	96	120
LED Chip	Samsung 5630/2835											
Driver	Driver(made with name brand parts and certified by TUV Mark)											
Trunking Rail Core	5 core(normal light with 3 phase function)				7 core(3 phase function+Dali/1-10V Dim				11 core(3 phase function+Dali/dim+emergency)			
Wiring Information	L1/L2/L3+N+FG				L1/L2/L3+N+FG+Dim+/Dim-				L1/L2/L3+N+FG+Dim+/Dim-+EL1/EL2/EN1/EN2			
Color Option	Black				White				Silver			
Beam Angle	Sharp/25°		Narrow/60°		Wide/90°		Flat/140°		Asymetric		Double Asymetric	
Phototomatic Data Curve												
Lumen Efficacy(4000K)	152±2		153±2		154±2		119±2		149±2		152±2	
UGR	16		19		22		28		N/A		N/A	
CCT Option	3000K/4000K/5000K/6000K											
CRI	>Ra80											
Input Voltage	100-277VAC/220-240VAC											
Output Voltage	30-40VDC											
Inrush Current	40A											
Power Factor	0.95											
Max Current	16A											
Service Life	60,000hours(L70)											
B Rate	B 10(Based on 50,000 hours)											
Dimming Function	DALI/1-10V/Switch Dim											
Emergency Function	Emergency Light								Ni-MH Battery			
	6W				12W				1800mA		3600mA	
IP Grade	IP20											
Packing Info(Trunking)	Size:77*45*12cm Weight:6kg 5 pcs per box				Size:164*47*16cm Weight:11.2kg 10 pcs per box							
Packing Info(Luminaire)	Size:66*45*14cm Weight:8.5kg 5 pcs per box				Size:149*40*24cm Weight:16.8kg 10 pcs per box							
Ambient temperature ta(at life time 60,000h)	-20-40℃											
Storage temperate ts	-40-85℃											
Certification	          											

Tel.:+49(0)711-60 17 110 Fax.:+49(0)711-60 17 11 11 Website: www.ledlum.com Email: info@tfe.com

ab Zentrallager Öhringen Stand März 2015 V-Kasse Einzug ÜBW Netto Netto